

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8797-8)

Set a fir post, 4 ft. long, 4" sq., 24" in the ground for the cor. to Secs. 14, 15, 22, & 23, marked T32S R8W S14 on NE, S23 on SE, S22 on SW, and S15 on the NW, also 3 notches on the S and 2 notches on the E angles of same, and from which
A laurel, 8" dia., bears N.35°E., 95 lks., mkd: T32S R8W S14 BT.
A laurel, 8" dia., bears S.60°E., 14 lks., mkd: T32S R8W S23 BT.
A chinquapin, 10" dia., bears S.70°W., 29 lks., mkd: T32S R8W S22 BT.
A pine, 40" dia., bears N.42°W., 163 lks., mkd: T32S R8W S15 BT.

Milner Larson, PE 3642 - Aug. 11, 1954 - C.S. File 41/289

I find a Sugar pine, 50" dia., N.42°W., 163 lks., marked as described (this tree was cut for a logging landing)
A chinquapin sprout, bears S.70°W., 29 lks.
A laurel sprout, bears S.60°E., 14 lks.
A laurel sprout, bears N.35°E., 95 lks.,
From these trees:
I drive a 1" iron bolt 30" in length, 24" in the ground, From which:
A fir 17" dia., bears N.35½°E., 42.6 ft. mkd: 3642 BT.
A fir 12" dia., bears S.79½°W., 47.0 ft. mkd: 3642 BT.
A Sugar pine, 22" dia., bears S.57½°W., 86.1 ft., mkd: 3642 BT.
A Fir 12" dia., bears N.57½°W., 46.9 ft., mkd: 3642 BT.
Decl 19°30'E.

Fd. ok by DCSO, JMP, 4/23/1968 - C.S. file 54/65-51

BLM dependent resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Group #821 & 876, surveyed July 1973/July 1975 - (DCSO records Vol. 40 Page(s) 15982)

The cor. of secs. 14, 15, 22, and 23, perpetuated and recorded by Larson, in 1954, monumented with an iron bolt, ¾" firmly set, projecting 6" above ground, from which the remains of the original bearing trees:
A chinquapin root crown, bears S.70°W., 29 lks.
A sawed sugar pine stump, 50" dia., bears N.42°W., 163 lks., with old axe marks visible.
and bearing trees mkd. by Larson continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A fir, 26" dia., bears N.35½°E., 66 lks., with healed double blaze.

A fir, 20" dia., bears S.79½°E., 72 lks., with healed double blaze.

A sugar pine, 30" dia., bears S.57½°W., 131½ lks., with healed double blaze.

A fir, 24" dia., bears N.57½°W., 72 lks., with healed double blaze.

At the corner point

Set an iron post, 28 ins, long, 2½" dia., 22" in the ground, directly over iron bolt, with brass cap mkd.

T32S R8W
S 15 | S 14
S 22 | S 23
1975

Fd. Ok by DCSO, 10/21/1992 - C.S. File 64/39-3

Ron Quimby - Crew: J. Leonard & N. Fromdahl - 11/2013 - C.S. File 65/80-41

Found - 2½" I.pipe with brass cap (properly mkd)
30" Fir N.35°E., 43.6 ft. healed face.
26" Fir S.79°E., 47.5 ft. healed face.
36" S.Pine S.57°W., 86.8 ft. healed face.
28" Fir N.57°W., 47.5 ft. healed face.
New - Set alum. post 2' west. Re-tag bearing trees.
Note - Area burnt 8/2013
Compass decl. 15°E.

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2741; Surveyed March/April 2014 - (DCSO records Vol. 58 Page(s) 23259)

The cor. of secs. 14, 15, 22, & 23, monumented with an iron post, 2½" dia., firmly set, projecting 4" above the ground, with brass cap (properly) mkd.

from which the remains of BTs mkd. by Larson, in 1954

A fir, 40" dia., bears N.35½°E., 43.6 ft., with a healed double blaze.

A fir, 30" dia., bears S.79½°E., 47.5 ft., with a healed double blaze.

A sawed sugar pine stump, 41" dia., bears S.57½°W., 86.8 ft., with a healed blaze.

A fir, 41" dia., bears N.57½°W., 47.5 ft., with a healed double blaze.

Alongside the iron post is a bolt, ¾" dia., with 1" nut, firmly set, projecting 5" above the ground.