

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8799)

Set a fir post, 4 ft. long, 4" sq., 24" in the ground for the cor. to secs. 10, 11, 14, & 15, marked T32S R8W S11 on NE, S14 on SE, S15 on SW, and S10 on the NW faces, also 4 notches on the S and 2 notches on the E angles, and from which

- A laurel, 12" dia., bears N.40°E., 100 lks., mkd: T32S R8W S11 BT.
- A fir, 36" dia. bears S.12°E., 54 lks mkd: T32S R8W S15 BT
- A fir, 36" dia. bears S.50°W., 41 lks mkd: T32S R8W S10 BT
- A fir, 36" dia. bears N.30°W., 36 lks mkd: T32S R8W S14 BT

Lorne Swearingen - For: Robert Dollar Co. - Witness: Robert A Harris & Milner Larson - April 15, 1960 - C.S. File 51/63-3

Found in very poor condition. The BTs for Secs. 10, 14 & 15 were fir snags which had been bark scribed & a fire had destroyed the scribing on all except the tree for Sec. 14 which had some scribing visible. The BT for sec. 11 had been a laurel but only a stub remained.

I set the corner from the remaining evidence & mkd it a 1 1/4" (OD) iron pipe driven 20" in the ground from which I referenced:

- 30" D.Fir N.68 1/2°E., 74.3 ft. mkd: S11, 4186 BT.
- 6" Tan Oak S.62 1/4°E., 30.4 ft., mkd: S14 4186 BT.
- 36" D.Fir S.11°W., 58.2 ft., mkd: S15 4186 BT.
- 8" Tan Oak N.63 1/2°W., 9.6 ft. mkd: S10 4186 BT.

Fd. Ok by DCSO, JMP - 4/30/1968 - C.S. File 54/65-5

BLM dependent resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Group #821 & 876, surveyed July 1973/July 1975 - (DCSO records Vol. 40 Page(s) 15985)

The cor. of secs. 10, 11, 14 & 15, determined from the remains of the original bearing trees:

- A sawed fir stump, 36" dia., bears S.30°E., 36 lks., no marks visible.
- A fir snag, 36" dia., bears S.12°W., 54 lks., no marks visible.
- A sawed and decayed fir stump, 24" dia., bears N.50°W., 37 lks., no marks visible. (Record, 41 lks.)

and BTs mkd. by Swearingen, in 1960

- A fir, 30" dia., bears N.71°E., 115 1/2 lks., with healed double blaze.

continued next page

