

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8800-1)

-----  
A Fir, 6" dia., for the cor., to secs. 2, 3, 10, & 11, which I marked T32S R8W S2 on NE face, S11 on SE, S10 on SW, & S3 on the NW faces, also 5 notches on the S & 2 notches on the E angles of same, from which

- A fir, 5" dia., bears N.70°E., 37 lks. mkd: T32S R8W S2 BT
- A fir, 14" dia. bears S.20°E., 15 lks mkd: T32S R8W S11 BT
- A fir, 10" dia. bears S.70°W., 13 lks mkd: T32S R8W S10 BT
- A fir, 8" dia., bears N.30°W., 7 lks., mkd: T32S R8W S3 BT

Douglas Co. Surveyors Office - John Powell - 5/1968 - C.S. file 54/65-10

-----  
Reported as not found.  
Found E-W blazes  
N-S blazes  
Also a lot of trees cut into probably destroying bark scribing. BTs were small trees.

BLM dependent resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Group #821 & 876, surveyed July 1973/July 1975 - (DCSO records Vol. 40 Page(s) 15986-7)

-----  
Point for the cor. of secs. 2, 3, 10, & 11 proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 22" in the ground, with brass cap marked:

T32S	R8W
S 3	S 2
S 10	S 11
1975	

from which

- A fir, 12" dia. bears N.9½°E., 25 lks. mkd: T32S R8W S2 BT
- A fir, 7" dia. bears S.83°E., 42½ lks mkd: T32S R8W S11 BT
- A fir, 6" dia. bears S.85½°W., 28 lks mkd: T32S R8W S10 BT
- A sugar pine, 10" dia., bears N.28°W., 48 lks., mkd: T32S R8W S3 BT.

Fd. Ok by M. Smalley, July 2003 - M143-2  
Fd. Ok by D. Edwards, 8/2005 - M148-31

Ron Quimby - Crew: N. Fromdahl & R. Olsen - 7/2014 - C.S. File 65/82-58

-----  
Found - BLM brass cap properly mkd.  
18" Fir N.9°E., 16.5 badly burnt cont. next pg

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias	Description

New -  
13" Fir S.83°E., 78.1 ft. badly burnt.  
15" Sugar pine N.28°W., 31.7 badly burnt.  
14" Fir S.85°W., 18.5 ft. vis. scribed.  
2 BLM ref. mons.  
BLM alum. cap bears N.30°E., 24.24' from corner  
(bearing per BLM e-mail: N.30°13'53"E., 24.24 ft)  
Cap mkd: BLM CADASTRAL SURVEY USDI 2014 T32S R8W  
RM S2 ✓ 24.24 FT. TO COR.  
BLM alum. cap bears S.79°E., 18.22' from corner  
(bearing per BLM e-mail: S.78°57'37"E., 18.22 ft)  
Cap mkd: BLM CADASTRAL SURVEY DOI 2014 T32S R8W  
RM ^ 18.22 FT. TO COR.  
14" Madrone N.84°W., 46.8' scribed T32S R8W S3 BT.  
14" Madrone S.40°W., 92.2' scribed T32s R8W S10 BT.  
Compass decl. 15½°E.

BLM resurvey by Brandon G Courtright, Cadastral Surveyor,  
under Group No. 2754, surveyed May/July 2014 - (DCSO records,  
Vol. 58 page(s) 23371-2)

-----  
The cor. of secs. 2, 3, 10, & 11, monumented with an iron  
post, 2½" dia., firmly set, projecting 9" above ground, with  
a brass cap (properly) mkd.  
from which the remains of the bearing trees mkd. by Roseberry  
and Aanrud in 1973-75  
A charred fir snag, 18" dia., bears N.9½°E., 16.5 ft.,  
with a healed blaze.  
A charred fir snag, 14" dia., bears S.83°E., 28.1 ft.,  
with a healed blaze.  
A charred fir snag, 15" dia., bears S.85½°W., 18.5 ft.,  
with a healed blaze.  
A charred pine snag, 15" dia., bears N.28°W., 31.7 ft.,  
with a healed blaze.  
and new reference monuments  
An alum. drive rod, 36" long, ¾" dia., driven 31" in the  
ground for a reference monument, bears N.30°14'35"E.,  
24.24 ft., with alum. cap mkd. RM T32SR8W 24.24 FT TO  
COR S2 2014, and an arrow pointing to the cor.  
An alum. drive rod, 36" long, ¾" dia., driven 32" in the  
ground for a reference monument, bears S.78°58'15"E.,  
18.22 ft., with alum. cap mkd. RM T32SR8W 18.22 FT TO  
COR S11 2014, and an arrow pointing to the cor.