

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 35 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8770)

Set a Laurel post 3" sq., 3 ft. long, 20" in the ground mkd. SC ¼ S for the ¼ sec. cor., from which
A Laurel 7" dia., bears N.16°E., 30 lks. dist. mkd. SC ¼ S BT.
A Laurel 8" dia., bears S.42°E., 22 lks. dist. mkd. SC ¼ S BT.

BLM Resurvey by Norman D. Price, U.S. Surveyor, Under instructions dated Sept. 22, 1916 - (DCSO records Vol. 21 Page(s) 8854)

Find no evidence of the cor. post established for standard ¼ cor. of sec. 35.
True point for cor. established from original bearing trees. At exact cor. point.
Set a granite stone 15x8x6 ins., 10" in the ground, for standard ¼ cor. of sec. 35, mkd. SC ¼ on N. face.
The old bearing trees being in poor condition, I obliterate markings on same and take new bearing trees as follows:
A Fir 36" dia., bears N.55°E., 90 lks. dist. mkd. SC ¼ S35 BT.
A Pine 18" dia., bears N.1°W., 64 lks. dist. mkd. SC ¼ S35 BT.

Ronald Brandt, L.S. 841 - For: The Robert Dollar Co. - 6/9/69 - Witness: Marvin Van Norman - C.S. File 51/68-10 Copy in C.S. File 54/65-77

Found - Sugar Pine BT 34" N.01°W., 42.2 ft.
Fir BT 38" N.55°E., 59.4 ft.
The brass cap and iron pipe removed by logging operation.
Reset - The brass cap and iron pipe according to the information called for. All bearings were taken with a staff compass, Magnetic Variation 19½° E. Distances were measured with a steel tape.

Cont. next page

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 35 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - John M. Powell, and crew -
May 1968 - C.S. File 54/65-69

Found - 18" Pine, now 34", N.1°W., 42.2 ft., tree opened,
"1/4" visible.

36" D.Fir now 38", N.55°E., 59.4 ft., shows good
scar.

15 x 8 x 6 stone at 1/4 corner, no marks.

Set Brass cap at cor. mkd: County Surveyors Office 1968
Doug. Co.

R8W T32S 1/4 S 35
T33S

Jos. Co.

Bearing trees all OK, tagged same.