

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8796-7)

Set a chinquapin post, 3 ft. long, 3" sq., 20" in the ground, for ¼ sec. cor., marked ¼ S on N side for the ¼ sec. cor. from which

 A laurel, 8" dia., bears N.25°E., 60 lks., mkd: ¼ S BT.
 A fir, 10" dia., bears S.60°E., 9 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John Powell - 3/1968 - C.S. File 54/65-38

Reported as not found.
Found small laurels chopped into.
Also location tag set by transit & chain? 1956.
No evidence of ¼ cor. after good search.

Ron Quimby - For: Roseburg Resources - 2/2014 - M167-22

Set - 5/8" by 30" iron rod with 2" aluminum cap mkd "ROSEBURG RESOURCES COMPANY" from which:

 21" fir blazed & scribed "BT ¼ S26" bears S.40°E., 36.6 ft.
 8" fir blazed & scribed "BT ¼ S26" bears S.6°W., 8.8 ft
 7" fir blazed & scribed "BT ¼ S23" bears N.22°E., 31.5 ft.
 36" fir blazed & scribed "BT ¼ S23" bears N.75°W., 44.0 ft.

1