

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 14 & 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2741; Surveyed March/April 2014 - (DCSO records Vol. 58 Page(s) 23262-3)

The ¼ sec. cor. of secs. 14 & 23, monumented with an iron post, 2½" dia., firmly set, projecting 5" above the ground, with brass cap (properly) mkd. from which BTs mkd. by Swearingen, in 1960
 A madrone, 11" dia., bears N.40½°E., 16.3 ft., with a healed double blaze. (Record, 17.2 ft.)
 A fir, 45" dia., bears S.19°E., 42.6 ft., with a healed double blaze. (Record, 43.6 ft.)
Alongside the iron post is a steel rod, 7/8" dia., firmly set, projecting 10" above the ground.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 5/21/2025 - C.S. File 67/60-37

Found - 3¼" BLM Brass cap proj. 5".
 12" Madrone N.40½°E. 16.3 ft healed double blaze.
 47" D.Fir S.19°E. 45.5 ft (Rec 42.6) healed double blaze.
 7/8" steel rod along side proj. 8"
New - 9" tan oak S.48°E. 23.0 ft scribe ¼ S23 CS BT on double blaze.
Compass decl. 14½°E.
OCRS COORDINATE SYSTEM
COTTAGE GROVE-CANYONVILLE ZONE
N. -18280.281 E. 88989.453