

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 540440

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2741; Surveyed March/April 2014 - (DCSO records Vol. 58 Page(s) 23263)

-----  
Point for the center ¼ sec. cor. of sec. 14, at intersection of the N and S center line with the E and W center line. Set a stainless steel post, 28" long, 2½" dia., 23" in the ground, with brass cap mkd.

T 32 S R 8 W  
C ¼ S 14  
2014

from which

An iron rod, 24" long, 5/8" dia., set 23" in the ground for a reference monument, bears N.2°07'05"E., 34.20 ft., with aluminum cap, 1½" dia., mkd. RM C ¼ S14 34.20 FT 2014, and an arrow pointing to the cor.

An iron rod, 24" long, 5/8" dia., set 23" in the ground for a reference monument, bears S.75°35'38" W., 30.10 ft., with aluminum cap, 1½" dia., mkd. RM C ¼ S14 30.10 FT 2014, and an arrow pointing to the cor.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.