

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8800)

A Laurel, 6" dia., which I marked ¼ S on N side for the ¼ sec. cor. and from which

A laurel, 10" dia., bears S.15°E., 16 lks., mkd: ¼ S BT.

A laurel, 8" dia., bears N.20°W., 17 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John Powell - 5/1968 - C.S. file 54/65

Reported as not found.

3 sm laurels seems to come in burn. Good E-W blazed line.

BLM dependent resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Group #821 & 876, surveyed July 1973/July 1975 - (DCSO records Vol. 40 Page(s) 15984-5)

Point for the ¼ sec. cor. of secs. 11 & 14, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground with brass cap marked:

T32S R8W

¼ S 11

S 14

1975

from which

A fir 6" dia., bears N.65°E., 57 lks., mkd: ¼ S11 BT.

A fir, 25" dia., bears S.29½°W., 48½ lks., mkd: ¼ S14 BT.

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2741; Surveyed March/April 2014 - (DCSO records Vol. 58 Page(s) 23262)

The ¼ sec. cor. of secs. 11 & 14, monumented with an iron post, 2½" dia., firmly set, projecting 6" above the ground, with brass cap (properly) mkd.

from which the remains of BTs mkd. by Roseberry & Aanrud in 1973-75

A burnt fir snag, 9" dia., bears N.65°E., 37.6 ft., with a healed blaze.

A burnt fir stump, size indeterminate, bears S.29½°W., 32.0 ft., with a healed blaze.

and new accessories

An iron rod, 24" long, 5/8" dia., set 20" in the ground for a reference monument, bears S.25°29'13" E., 49.59 ft., with aluminum cap, 1½" dia., mkd. RM T32S R8W ¼ S14 49.59 FT TO COR 2014, and an arrow pointing to the cor.

continued next page

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

An iron rod, 24" long, 5/8" dia., set 20" in the ground for a reference monument, bears N.81°36'01"W., 29.19 ft., with aluminum cap, 1 1/2" dia., mkd. RM T32S R8W 1/4 S11 29.19 FT TO COR 2014, and an arrow pointing to the cor.

Ron Quimby - Crew: N. Fromdahl & R. Olsen - 8/2014 - C.S.
File 65/86-1

Found - BLM Brass cap (properly mkd)
8" Fir N.65°E., 37.6 ft. dead & burnt.
13"x2' tall stump S.29°W., 32.0 burnt.
Set - 4 I.Rods with plastic cap:
North 3.0 ft.
East 3.0 ft.
South 2.0 ft.
West 5.0 ft.
Note - Area badly burnt 7/2013
Compass decl. 15 1/2°E.