

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 540640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Howard Johnstone - For: Roseburg Lumber Co. - April 1980 - M83-26

-----  
Set - 5/8"x30" iron rod & alum. cap.  
8" Fir bears N.87°W., 35.0 ft.  
8" Fir bears S.20°E., 31.0 ft.

Ron Quimby - J. Leonard & N. Fromdahl Crew - 9/2013 - C.S. File 65/80-12

-----  
Found - 5/8" I.Rod & alum. cap  
Set - Alum. post 2' north & 2' east.  
Note - Area burnt 7/2013  
Compass decl. 15½°E.

BLM resurvey by Brandon G Courtright, Cadastral Surveyor, under Group No. 2754, surveyed May/July 2014 - (DCSO records, Vol. 58 page(s) 23378-9)

-----  
The center ¼ sec. cor. of sec. 2, established by Johnstone, in 1980, and is accepted as the cor., monumented with an iron rod, 30" long, 5/8" dia., loosely set, projecting 14" above ground, with alum. cap mkd. T32S R8W SEC2 C¼ 1980 LS498

At the corner point  
Set a stainless steel post, 28" long, 2½" dia., 23" in the ground, in a collar of stone, with brass cap mkd.

T 32 S R 8 W  
C ¼ S 2  
2014

from which new reference monuments

An iron rod, 5/8" dia., 30" long, driven 24" in the ground for a reference monument, bears N.07°55'46"E., 12.13 ft., with alum. cap mkd. RM2 T32S R8W C¼ S2 12.13 FT TO COR 2014, and an arrow pointing to the cor.

An iron rod, 5/8" dia., 30" long, driven 25" in the ground, bears N.73°12'11"E., 17.69 ft., with alum. cap mkd. RM1 T32S R8W C¼ S2 17.69 FT TO COR 2014, and an arrow pointing to the cor.

Deposit the iron rod inside the stainless steel post.