

PRIMARY CORNER DESCRIPTION Standard Cor. for Secs. 35 & 36 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8769)

Set a Laurel post 4" sq., 24" in the ground mkd. S C T32S R8W on N.; S36 on E.; S35 on W. faces and 5 notches on the W. and 1 notch on the E. faces, for the standard cor. to secs. 325 and 36, and from which

A Fir 15" dia., bears N.68°E., 35 lks. dist. mkd. SC T32S R8W S36 BT.

A Laurel 8" dia., bears S.52°E., 34 lks. dist. mkd. SC T33S R8W S BT.

A Fir 15" dia., bears N.24°W., 28 lks. dist. mkd. SC T32S R8W S35 BT.

BLM Resurvey by Norman D. Price, U.S. Surveyor, Under instructions dated Sept. 22, 1916 - (DCSO records Vol. 21 Page(s) 8853)

The standard cor., which is a Laurel post, 4x4 ins., badly decayed, marked and witnessed as described by the surveyor general, SE. bearing tree badly decayed. Alongside of post. Set a granite stone 20x12x10 ins., 15" in the ground, mkd. SC on N.; with 5 grooves on W. and 1 groove on E. face.

Milner L. Larson - Eng. #3642 - Nov. 22, 1954 - C.S. File 41/320

No evidence of the cor. post remains. True point for corner established from original bearing trees:

A Fir stump 30" dia., bears N.31°46'E., 9.4 ft. dist., an old notch and a "BT" carved with knife are all that remain.

A Fir stump 21" dia., bears N.49°08'W., 23.2 ft. dist., this stump badly rotted out.

A Fir 26" dia., bears S.9°39'E., 12.6 ft. dist., parts of original scribing visible.

At point for the corner, I drive a 1¼" Iron pipe 30" long, 24" in the ground, and take new BTs as follows:

A Fir 11" dia., bears N.27°24'E., 14.7 ft. dist. mkd. 3642 BT.

A Fir 14" dia., bears N.33°27'W., 17.4 ft. dist. mkd. 3642 BT.

A Live Oak 17" dia., bears S.0°13'W., 31.4 ft. dist. mkd. 3642 BT.

(Cont. Next Page)

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Standard Cor. for Secs. 35 & 36 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - John M. Powell, and crew - May 1968 - C.S. File 54/65-70

Found no trace of corner stone. Larson said he renewed this corner in 1954, but I do not find any evidence of his corner. Found - Orig. 15" now 20" D.Fir S.68°E., 23.1 ft., shows good scar.

Orig. 8" now 12" Laurel S.52°E., 22.4 ft.

Orig. 15" D.Fir, tree opened, N.24°W., 18.5 ft., scribe marks visible.

Set Brass cap at cor. mkd: County Surveyors Office 1968

Doug. Co.

R8W	T32S	S 35	S 36
	T33S	S 1	

Jos. Co.

Bearing trees OK, and tagged.

Corner lies 54.1 ft. E. of the C.C. of secs. 1 & 2, T33-8

BLM Dependent resurvey by Arthur R. Rambo, Cadastral Surveyor under Group No. 2179, surveyed July/Nov. 2007 - (DCSO records, Vol. 55 Page(s) 21612-3)

The standard cor. of secs. 35, and 36, on the S. bdy. of the Tp. perpetuated by the Douglas County Surveyor's Office, in 1968, monumented with an iron post, 1½" dia., firmly set, projecting 12" above the ground, with the stone set by Price, 20x12x10", lying loose alongside, mkd. C on a face, 1 groove on a face, and 5 grooves on another face, brass cap (properly) mkd.

from which the original bearing trees

A fir, 28" dia., bears N.68°E., 21.3 ft., with a healed blaze. (Record, 23.1 ft.)

A madrone, 14" dia., bears S.45¼°E., 22.4 ft., with opened and rotted blaze, no marks visible. (Record, S.52°E.)

A fir, 22" dia. bears N.24°W., 18.5 ft with a healed blaze
No evidence was found of the perpetuation by Milner L. Larson, Registered Professional Engineer No. 3642, in 1954, recorded in C.S. File 41/320, in the Douglas County Surveyor's Office.

Fd. as per record, 11/2015 by Neil Hibbs