

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8781)

Set a stone 14x12x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on West face, from which
A fir, 42" dia., bears S.40°E., 11 lks., mkd: ¼ S BT.
A live oak, 7" dia., bears N.66°W., 33 lks., mkd: ¼ S BT.

Milner L. Larson, PE 3642 - Nov. 22, 1954 - C.S. File 41/320

At 2548.1 ft. from the sec. cor. to secs. 25, 26, 35, & 36, I drive a 1¼" iron pipe 30" long 24" in the ground.
From which
A Fir, 8" dia., bears S.82°39'E., 36.4 ft.
A fir, 15" dia., bears S.76°59'W., 36.2 ft.

Douglas Co. Surveyors Office - John M. Powell - 4/1968 - C.S. File 54/65-36

Reported as not found.
This cor. seems to fall in old logging Rd. Location tag at 2500.00; corner at 2548 south of 25, 26, 35, & 36.

Neil Hibbs - For: Plum Creek Timber - 11/2015 - M170-21

Set - 5/8"x15" iron rod in rock (drilled)
36" cedar bears S.71°W., 45.0' scribed "¼ S 35" "BT" w/BT tag, face painted red.
24" cedar bears S.22½°W., 30.2' scribed "¼ S 35" "BT" w/BT tag, face painted red.