TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8788)

Set a Chinquapin post, 40" long, 4" sq., 20" in the ground, for ¼ sec. cor., marked ¼ S on W side and from which
A fir, 8" dia., bears S.58°E., 207 lks., mkd: ¼ S BT.
A chinquapin, 8" dia., bears S.89°W., 22 lks., mkd: ¼ S BT

Douglas Co. Surveyors Office - John M. Powell - 4/1968 - C.S. File 54/65-49

Reported as not found.
Very old N-S brushed line. A few firs about 30-40", BTs 8". Found no evidence worth investigating. No good calls to work from.

BLM dependent resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Group #821 & 876, surveyed July 1973/July 1975 - (DCSO records Vol. 40 Page(s) 15975-6)

Point for the ¼ sec. cor. of secs. 13 & 14, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground with brass cap marked: T32S R8W

¼
S 14|S 13
1975

from which
A fir, 15" dia., bears S.20°E., 11 lks., mkd: ¼ S13 BT.
A fir, 12" dia., bears N.37°W., 25 lks., mkd: ¼ S14 BT.

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 2741; Surveyed March/April 2014 - (DCSO records Vol. 58 Page(s) 23263-4)

The ¼ sec. cor. of secs. 13 and 14, monumented with an iron post, 2½" dia., firmly set, projecting 7" above the ground, with brass cap (properly) mkd.
from which BTs mkd. by Roseberry and Aanrud in 1973-75
A fir, 25" dia. bears S.20°E., 7.3 ft. with a healed blaze
A fir, 21" dia. bears N.37°W., 16.5 ft with a healed blaze

NAD 1983 (2011)
Latitude: 42°47'23.18"N Longitude: 123°36'11.82"W