

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8788)

A Laurel, 5" dia., which I marked T32S R8W S12 on NE; S13 on SE S14 on the SW and S11 on the NW faces also 4 notches on the S and 1 notch on the E angle of same for the cor. to secs. 11, 12, 13, and 14, from which

 A laurel, 5" dia., bears N.22°E., 51 lks., mkd: T32S R8W S12 BT.

 A laurel, 5" dia., bears S.52°E., 44 lks., mkd: T32S R8W S13 BT.

 A laurel, 5" dia., bears S.21°W., 10 lks., mkd: T32S R8W S14 BT.

 A laurel, 5" dia., bears N.60°W., 36 lks., mkd: T32S R8W S11 BT.

Douglas Co. Surveyors Office - John Powell - 4/1968 - C.S. File 54/65-2

Reported as not found.
 Found Point of intersection of N-S-E-W lines. Location tag at approx. cor. No trace of trees. Area Cut, also burnt years ago.

BLM dependent resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Group #821 & 876, surveyed July 1973/July 1975 - (DCSO records Vol. 40 Page(s) 15976)

Point for the cor. of secs. 11, 12, 13, & 14 proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground, with brass cap marked:

T32S	R8W
<u>S 11</u>	<u>S 12</u>
S 14	S 13
1975	

from which

 A sugar pine, 22" dia., bears N.74½°E., 25 lks., mkd: T32S R8W S12 BT.

 A fir, 10" dia., bears S.37°E., 38½ lks., mkd: T32S R8W S13 BT.

 A fir, 15" dia., bears S.68½°W., 58 lks., mkd: T32S R8W S14 BT.

 A fir, 17" dia. bears N.9½°W., 37 lks mkd: T32S R8W S11 BT

continued next page

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Ron Quimby - Crew: N. Fromdahl & R. Olsen - 8/2014 - C.S.
File 65/86-2

Found - BLM brass cap (properly mkd)
5' tall 26" sugar pine stump N.74°E., 16.5 ft.
18" Fir S.37°E., 25.4 ft. good scar.
32" Fir S.68°W., 38.3 ft. good scar.
30" Fir N.9°W., 24.4 ft. good scar.
New - A 16" W.Fir N.88°E., 52.0 ft scribed T32S R8W S21 BT
Note - Area Burnt 7/2013
Compass decl. 15½°E.

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor,
under Group No. 2741; Surveyed March/April 2014 - (DCSO
records Vol. 58 Page(s) 23261)

The cor. of secs. 11, 12, 13, & 14, monumented with an iron
post, 2½" dia., firmly set, projecting 6" above the ground,
with brass cap (properly) mkd.

from which the remains of BTs mkd. by Roseberry & Aanrud in 1973-75

A sawed sugar pine stump, 24" dia., 6 ft. high, bears
N.74½°E., 16.5 ft., with a portion of a healed blaze
visible.

A fir, 20" dia., bears S.41°E., 25.4 ft., with a healed
blaze. (Record, S.37°E.)

A fir, 34" dia., bears S.68½°W., 38.3 ft., with a healed
blaze.

A fir, 31" dia., bears N.9½°W., 24.4 ft., with a healed
blaze.

and a new bearing tree

A fir, 14" dia., bears N.88°E., 52.0 ft., mkd. T32S R8W
S12 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail)
driven at the base right side-center.