

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8790)

-----  
A Laurel, 5" dia., which I mark  $\frac{1}{4}$  S on W side for the  $\frac{1}{4}$  sec. cor., from which  
    A laurel, 5" dia., bears N.10°E., 10 lks., mkd:  $\frac{1}{4}$  S BT.  
    A laurel, 5" dia., bears N.14°W., 9 lks., mkd:  $\frac{1}{4}$  S BT.

Douglas Co. Surveyors Office - John Powell - 4/1968 - C.S. file 54/65-2

-----  
Reported as not found.  
N-S line, 3 small laurels on US-R. Dollar line.

BLM dependent resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Group #821 & 876, surveyed July 1973/July 1975 - (DCSO records Vol. 40 Page(s) 15978)

-----  
Point for the  $\frac{1}{4}$  sec. cor. of secs. 11 & 12, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2 $\frac{1}{2}$ " dia., 21" in the ground, & in a mound of stone, 2 ft. base, to top, with brass cap mkd:

T32S R8W  
           $\frac{1}{4}$   
S 11|S 12  
      1975

from which  
    A fir, 20" dia., bears S.81°E., 107 lks., mkd:  $\frac{1}{4}$  S12 BT.  
    A fir, 27" dia., bears N.52°W., 140 lks., mkd:  $\frac{1}{4}$  S BT.