

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8790)

Set a laurel post 4 ft. long, 4" sq., 24" in the ground for the cor. to secs. 1, 2, 11, & 12, mkd T32S R8W S1 on NE face, S12 on SE face; S11 on SW & S2 on the NW faces, also 5 notches on S & 1 notch on the E angles of the same and from which

A laurel, 12" dia., bears N.40°E., 55 lks., mkd: T32S R8W S1 BT.

A laurel, 10" dia., bears S.30°E., 36 lks., mkd: T32S R8W S12 BT.

A fir, 30" dia. bears S.20°W., 66 lks mkd: T32S R8W S11 BT

A fir, 24" dia. bears N.40°W., 57 lks. mkd: T32S R8W S2 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - April 1968 - C.S. File 54/65-30

Found - Unrecorded 1" Iron pipe, not at record bearing & distance (Iron pipe bears N.20°E., 1.0 ft.)
30" D.Fir now 50", S.20°W., 43.6 ft., faint bark scribe.

Set - Brass cap at cor. mkd: County Surveyors T32S R8W
Office S 2 | S 1
1968 S 11 | S 12

New BTs- 7" Tan Oak N.85°W., 14.2 ft. mkd: T32S R8W S2 CS BT.

16" D.Fir N.22°E., 26.8 ft., mkd: T32S R8W S1 CS BT.

15" Tan Oak S.77°E. 18.7 ft. mkd: T32S R8W S12 CS BT

Reblazed & bark scribed -

50" D.Fir S.20°W., 43.6 ft., mkd: T32S R8W S11 CS BT

BLM dependent resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Group #821 & 876, surveyed July 1973/July 1975 - (DCSO records Vol. 40 Page(s) 15979)

The cor. of secs. 1, 2, 11, & 12 perpetuated and recorded by Powell, in 1968, monumented with an iron pipe, 1½" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A madrone, 13" dia., bears N.40°E., 51 lks., no marks visible. (Record, 53 lks.)

A fir, 57" dia., bears S.20°W., 66 lks., with scribe marks T32S visible on bark blaze. This tree was rescribed by Powell, with scribe marks T32S R8W S11 CS BT visible on bark blaze.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 1, 2, 11, & 12

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A fir root crown, size indeterminate, bears N.35°W., 59 lks. (Record, N.40°W., 57 lks.) and bearing trees mkd, by Powell

A fir, 17" dia., bears N.21°E., 40½ lks., with healed double blaze.

A tan oak, 16" dia., bears S.77°E., 27 lks. with scribe marks T32S R8W S12 CS BT visible on partially healed double blaze.

A tan oak, 7" dia., bears N.85°W., 21 lks., with scribe marks T32S R8W S2 CS BT visible on partially healed double blaze.

From this point, a point established by person(s) unknown monumented with an Iron pipe, 1¼" dia., firmly set, projecting 15", above ground, bears North, 0.015 chs.

FD BC & 4 BTs 4/1980 by Howard Johnstone, M83-25

Douglas Co. Surveyors Office - Ed Monrean & Randy Smith - 9/22/1992 - C.S. file 64/32-7

Found BC & BTs as recorded in 1975 BLM resurvey. No new accessories.

FD as per M83-25, except The Fir N.22°E., is a stump, by D. Edwards M164-73 - 3/2013

BLM resurvey by Brandon G Courtright, Cadastral Surveyor, under Group No. 2754, surveyed May/July 2014 - (DCSO records, Vol. 58 page(s) 23370)

The cor. of secs. 1, 2, 11, & 12, perpetuated by Powell, in 1968, monumented with an iron post, 1½" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd. from which the remains of the original bearing trees

A madrone, 18" dia., bears N.40°E., 33.7 ft., no marks visible.

A charred fir, 59" dia., bears S.20°W., 43.6 ft., with a healed blaze.

and the remains of the bearing trees mkd. by Powell, reported by Roseberry and Aanrud in 1973-75

A charred and rotting fir stump, 3 ft. tall, 28" dia., bears N.21°E., 26.7 ft., no marks visible.

A tan oak, 18" dia., bears S.77°E., 17.8 ft., with a partially healed blaze.

A tan oak, 10" dia., bears N.85°W., 13.9 ft., with a partially healed blaze.

From this cor., a point established by person(s) unknown, and was not utilized in the course of this survey, monumented with an iron pipe, 1 ¼" dia., firmly set projecting 15" above ground, bears N., 1.00 ft.