

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor under contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8793)

Set a stone 14x10x6", 10" in the ground for ¼ sec. cor. mkd. ¼ on the W face and from which

A pine, 18" dia., bears N.16°E., 105 lks., mkd: ¼ S BT.

A pine, 50" dia., bears N.35°W., 114 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & W. Penley - March/April 1968 - C.S. File 54/65-32

Found - 14x10x6 Stone at ¼ Cor., chisel marks visible, stone firmly in ground.

50" S.Pine, now 55" Snag, N.35°W., 75.2 ft

18" S.Pine, now 36", N.16°E. 69.3 ft., shows scar.

Set - Brass Cap at Cor. Mkd: County Surveyors T32S R8W Office, 1968 ¼ S 2|S 1

New BTs- 6" Live Oak N.10°W. 20.0 ft. mkd. ¼ S2 CS BT.

7" Live Oak S.27°E. 22.3 ft. mkd. ¼ S1 CS BT.

Note - This corner lies on fairly steep west slope.

BLM resurvey by Brandon G Courtright, Cadastral Surveyor, under Group No. 2754, surveyed May/July 2014 - (DCSO records, Vol. 58 page(s) 23371)

The ¼ sec. cor. of secs. 1 & 2, perpetuated by Powell, in 1968, monumented with an iron post, 1½" dia., firmly set, projecting 10" above ground, with a brass cap (properly) mkd. from which the remains of the original bearing trees

A charred and rotted pine stump, size indeterminate, bears N.16°E., 69.3 ft., no marks visible.

A charred and rotted pine stump, size indeterminate, bears N.35°W., 75.2 ft., no marks visible.

and the remains of bearing trees mkd. by Powell

A live oak snag, 8" dia., bears S.27°E., 22.3 ft., with illegible scribe marks visible on an open charred blaze.

A live oak snag, 9" dia., bears N.10°W., 20.1 ft., with a healed blaze.

and new reference monuments

A Berntsen® FENO monument, 24" long, 5/8" dia., driven 22" in the ground for a reference monument, bears N.57°13'21"E, 21.38 ft., with alum. cap (properly) mkd. RM1 T32S R8W ¼ S1 21.38 FT TO COR, and an arrow pointing to the cor.

continued next page

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Berntsen® FENO monument, 24" long, 5/8" dia., driven flush with surface of ground, for a reference monument, bears N.10°25'28"W, 17.39 ft., with alum. cap (properly) mkd. RM2 T32S R8W ¼ S2 17.39 FT TO COR, and an arrow pointing to the cor.