

PRIMARY CORNER DESCRIPTION Sec. cor. for 1 & 2; 35 & 36, T31-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor under contract # 456 dated July 28, 1882 (DCSO records Vol. 19 Pages 8097-98)

Set a Pine post 4" sq., 4 ft. long, 24" in the ground mkd. T31S R8W S36 on NE.; T32S S1 on the SE.; S2 on the SW.; and S35 on the NW. faces. Also 1 notch on the E. and 5 notches on the W. angles of same for the cor. to secs. 1, 2, 35 and 36, and from which

- A Pine 48" dia. bears N.62°E., 205 lks mkd T31S R8W S36 BT
- A Laurel 24" dia. bears S.76°E., 109 lks mkd T32S R8W S1 BT
- A Laurel 20" dia. bears S.14°W., 49 lks mkd T32S R8W S2 BT
- A Fir 15" dia., bears N.62°W., 120 lks mkd T31S R8W S35 BT

BLM Resurvey by James E. Jelley and James J. Carlson, Cadastral Surveyors, under Group #899, surveyed Aug. 1976/Nov. 1977 - (DCSO records Vol. 41 Page(s) 16184)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 31 S R 8 W
S 35 | S 36
S 2 | S 1
T 32 S
1977

from which

- A Fir 7" dia., bears N.17°E., 66 lks. mkd T31S R8W S36 BT.
- A Fir 6" dia., bears S.35½°E., 47 lks. mkd T32S R8W S1 BT.
- A Fir 14" dia., bears S.51½°W., 42 lks. mkd T32S R8W S2 BT
- A Fir 5" dia., bears N.22½°W., 35 lks. mkd T31S R8W S35 BT

BLM resurvey by Brandon G Courtright, Cadastral Surveyor, under Group No. 2754, surveyed May/July 2014 - (DCSO records, Vol. 58 page(s) 23368)

The cor. of secs. 1, 2, 35, & 36, monumented with an iron post, 2½" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd.

from which the BTs mkd. by Jelley and Carlson in 1976-77

- A fir, 14" dia., bears N.17°E., 43.6 ft., with a healed blaze.
- A fir, 15" dia., bears S.35½°E., 31.0 ft., with a healed blaze.
- A fir, 25" dia., bears S.51½°W., 27.7 ft., with a healed blaze.
- A fir, 10" dia., bears N.22½°W., 23.1 ft., with a healed blaze