

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 36 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8769)

Set a Laurel post 3" sq., 3 ft. long, 20" in ground for the 1/4 sec. cor., from which
A Laurel 10" dia., bears North, 32 lks. dist., mkd. 1/4 S BT
A Fir 32" dia., bears S.45°W., 30 lks. dist. mkd. 1/4 S BT.

BLM Resurvey by Norman D. Price, U.S. Surveyor, Under instructions dated Sept. 22, 1916 - (DCSO records Vol. 21 Page(s) 8852-53)

Find no evidence of the cor. post established for standard 1/4 cor. of sec. 36.
True point for cor. established from original bearing trees. At the exact cor. point
Set a granite stone 15x14x6 ins., 10" in the ground, for standard 1/4 cor. of sec. 36, marked SC 1/4 on N. face.
The old bearing trees being dead, I obliterate markings on same and take new bearing trees as follows:
A Fir 15" dia., bears N.55 1/2°E., 21 lks. dist. mkd. SC 1/4 S36 BT.
A Fir 18" dia., bears N.62°W., 37 lks. dist. mkd. SC 1/4 S36 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - May/June 1968 - C.S. File 54/65-72

Found - Corner stone 13x14x6, mkd. (SC).
Orig. 15" now 18" D.Fir, N.55 1/2°E., 13.9 ft., shows good scar.
Orig. 18" now 24" D.Fir, N.62°W., 24.4 ft., open and show scribing.

Set Brass cap at cor. mkd: County Surveyors Office 1968
Doug. Co.
R8W T32S
1/4 S 36
R8W T33S
Jos. Co.
Rescribe-24" D.Fir N.62°W., 24.4 ft. mkd. 1/4 S36 SC CS BT.
This corner lies on S. side of E-W cutting line approx. 85 ft. E. of creek.

Fd. OK, Jan. 6, 1996 by B. Shaner - M 123-17

continued next page

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 36 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Arthur R. Rambo, Cadastral Surveyor under Group No. 2179, surveyed July/Nov. 2007 - (DCSO records, Vol. 55 Page(s) 21611-2)

The standard ¼ sec. cor. of sec. 36, on the S. bdy. of the Tp., perpetuated by the Douglas County Surveyor's Office, in 1968, monumented with an iron post, 1½" dia., firmly set, projecting 10" above the ground, with the stone set by Price, 15 x 14 x 6", lying loose alongside, mkd. SC ¼ on a face, brass cap (properly) mkd.

from which bearing trees mkd. by Price

A fir, 22" dia., bears N.55½°E., 13.9 ft., with a healed blaze.

A fir, 26" dia., bears N.62°W., 24.4 ft., with a healed blaze.

The standard ¼ section corner of section 36, on the S. boundary of the Tp.:

Latitude: 42°44'24.39"N.

Longitude: 123°35'33.23"W.

Fd. as per record, 11/2015 by Neil Hibbs