

TOWNSHIP 32 RANGE 08 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION ¼ sec. of 36; & 31 of T32S R7W

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original GLO Survey by W.H. Byars - contract #420 dated Sept. 16, 1881 (DCSO records Vol. 20 Page(s) 8707)

Set - Laurel post, 4' long 4" sq. 15" in the ground, mkd. ¼ S on W face.

BT's- Cedar, 24" dia., bears N.40°E., 45 lks., mkd. ¼ S BT.
Laurel, 12" dia., bears N.80°W., 62 lks., mkd. ¼ S BT.

Bruce Shaner - 1/6/96 - M 123-17

Mon. Fd.-No evidence found. East line of sec. 36 was surveyed and corner was set by proportional measurement.

Mon. Set-I set a 3" Alum. cap on a 2½"x30" alum. pipe in the g r o u n d .

New BT's-12" D.Fir, scribed "¼ S36 BT", bears N.75°W., 17.8'.

14" D.Fir, scribed "¼ S36 BT", bears S.47°W., 35'.

16" D.Fir, scribed "¼ S31 BT", bears S.23°E., 18'.

16" D.Fir, scribed "¼ S31 BT", bears N.81°E., 43.2'.