

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24; 18 & 19, T32-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 420 survey dated Sept 16 1881 (DCSO records Vol. 20 Page(s) 8709)

-----  
Set a Laurel post 4½ ft. long, 4" sq., 18" in the ground, marked T32S R7W S18 on NE. face; S19 on SE. face; S24 on SW. face; R8W S13 on NW. face; for the corner to Secs. 13, 18, 19 and 24, from which

- A Laurel 10" dia., bears N.30°E., 81 lks. dist., mkd. T32S R7W S18 BT.
- A Laurel 5" dia., bears S.12°E., 51 lks. dist., mkd. T32S R7W S19 BT.
- A Fir 6" dia., bears S.55°W., 23 lks. dist., mkd. T32S R8W S24 BT.
- A Live Oak 6" dia., bears N.55°W., 81 lks. dist., mkd. T32S R8W S13 BT.


Fd. and used in GLO survey by Dickerson, Contract #474, dated May 1883 (DCSO records, Vol. 21 Page 8787)

GLO remonumentation by Hans W. Thielsen, under Group #350, Surveyed, Nov. 1958/July 1959 - (DCSO records Vol. 33 Page(s) 13659)

-----  
The Sec. cor., determined at record bearing and distance from the three remaining original bearing trees:

- A Madrone 16" dia., bears N.30°E., 81 lks. dist., no marks remaining on opened blaze.
- A Fir 24" dia., bears S.55°W., 23 lks. dist., with illegible scribe marks visible on an opened and burned blaze.
- A Live Oak 12" dia., bears N.55°W., 81 lks. dist., with scribe marks R8W S13 visible on opened blaze.

At the corner point  
Set an iron post, 3 ft. long, 1 in. dia., 28" in the ground, with brass cap marked T 32 S



- from which
- A Fir 18" dia., bears N.19°E., 85 lks. dist., mkd. T32S R7W S18 BT.
  - A Fir 9" dia., bears S.70½°E., 54 lks. dist., mkd. T32S R7W S19 BT.
  - A Fir 14" dia., bears S.72½°W., 75 lks. dist., mkd. T32S R8W S24 BT.

(Cont. Next Page)

