

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only, T32-10

| Alias | Description |
|-------|-------------|
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |
| _____ | _____ |

GLO survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8861)

Set a stone 14x12x10 ins., 10" in the ground for the ¼ sec. cor. mkd. ¼ on W. side, and from which
A Fir 30" dia., bears N.28°E., 34 lks. dist. mkd. ¼ S BT.
A Fir 40" dia., bears N.42°W., 25 lks. dist. mkd. ¼ S BT

GLO Survey by George S. Pershin, under Contract #728, Dated Dec. 20, 1900 - (DCSO records Vol. 21 Page(s) 8865)

To a point, 1.36 chs. N. and 2.10 chs. E. of old cor., which I totally obliterate.
Set a ston 15x12x10 ins., 10" in the ground for ¼ sec. cor. mkd. ¼ on W. face, from which
A Fir 40" dia., bears N.63°E., 24 lks. dist. mkd. ¼ S18 BT
A Fir 36" dia., bears N.72°W., 70 lks. dist. mkd. ¼ S13 BT

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8869-70)

Intersect the old ¼ sec. cor., which is a basalt stone, 15x12x10 ins., loosely set, mkd. and witnessed as described by the surveyor general. I change this cor. to refer to sec. 13 only and perpetuate it as follows: alongside the old cor. Set an iron post 3 ft. long, 1" dia., 26" in the ground for ¼ cor. of sec. 13, T32S R10W only, with brass cap mkd.

¼
S13
1917

from which
A Fir 40" dia., bears S.69°W., 64 lks. dist., mkd. ¼ S13 BT. (New BT)
A Fir 30" dia., bears N.60°W., 69 lks. dist. mkd. ¼ S13 BT. (Old BT)