

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13, T32-10

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8861-82)

A Fir 30" dia., which I marked T32S R9W S7 on NE.; S18 on SE.; R10W S13 on SW. faces, and S12 on NW. also 4 notches on S. and 2 notches on N. side of same, from which

- A Fir 48" dia., bears N.62°E., 43 lks. dist. mkd. T32S R9W S7 BT.
- A Fir 10" dia., bears S.5°E., 66 lks. dist. mkd. T32S R9W S18 BT.
- A Fir 8" dia., bears S.35°W., 39 lks. dist. mkd. T32S R10W S13 BT.
- A Fir 60" dia., bears N.26°W., 43 lks. dist. mkd. T32S R10W S12 BT.

GLO Survey by George S. Pershin, under Contract #728, Dated Dec. 20, 1900 - (DCSO records Vol. 21 Page(s) 8865)

To a point 2.12 chs. E. and 1.30 chs. N. of old cor., which I totally obliterate.

Set a stone 18x12x10 ins., 12" in the ground for cor. of secs. 12, 13, 7 and 18, marked with 4 notches on S. and 2 notches on N. edge, from which

- A Fir 24" dia., bears N.66°E., 12 lks. dist. mkd. T32S R9W S7 BT.
- A Fir 48" dia., bears S.48°E., 20 lks. dist. mkd. T32S R9W S18 BT.
- A Fir 72" dia., bears S.50°W., 14 lks. dist. mkd. T32S R10W S13 BT.
- A Fir 22" dia., bears N.42°W., 11 lks. dist. mkd. T32S R10W S12 BT.

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8870-71)

Intersect the old cor. of secs. 7, 2, 13 and 18, which is a basalt stone, 18x10x12 ins., loosely set, marked and witnessed as described by the surveyor general. I change this cor. to refer to secs. 12 and 13 only, and perpetuate it as follows: alongside the old cor.

Set an iron post 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 12 and 13, T32S R10W., only with brass cap mkd.

T32S		
S12		
S13		
R10W		1917

(Cont. Next Page)

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 100472

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13 only, T32-10

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

from which

A Fir 72" dia., bears S.50°W., 14 lks. dist., mkd. T32S
R10W S13 BT. (Old BT)

A Fir 24" dia., bears N.42°W., 11 lks. dist. mkd. T32S
R10W S12 BT. (Old BT)

Douglas Co. Surveyors Office - John M. Powell, and crew -
June 1967 - C.S. File 54/44-18

Found - 1917 GLO brass cap, properly mkd., at corner.
Original Corner stone.
72" D.Fir now 72" snag, S.50°W., 9.2 ft., opened and
found scribing.
24" now 28" Fir N.42°W., 7.2 ft., shows scar.

Rescribed:

28" D.Fir N.42°W., 7.2 ft., mkd. T32S R10W S12 CSBT
New Bt - 10" D.Fir S.85°W., 30.0 ft. mkd. T32S R10W S13 CS BT
Corner lies 50 ft. East of creek.