

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 12 only, T32-10

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8862)

-----  
Set a stone 20x10x10 ins., cliff of rocks, made stone mound, 2 ft. high, 3 ft. at base, about the same for the 1/4 sec. cor., marked stone 1/4 on W. side and from which  
A Fir 60" dia., bears S.50°E., 13 lks. dist. mkd. 1/4 S BT  
A Fir 20" dia., bears S.85°W., 8 lks. dist. mkd. 1/4 S BT.

GLO Survey by George S. Pershin, under Contract #728, Dated, Dec. 20, 1900 - (DCSO records Vol. 21 Page(s) 8866)

-----  
To a point 1.50 chs. N. and 2.20 chs. E. of old cor. which I obliterate.  
Set a stone 15x10x8 ins., 10" in the ground for 1/4 sec. cor. mkd. 1/4 on W. face, from which  
A Fir 14" dia., bears N.85°E., 73 lks. dist. mkd. 1/4 S7 BT.  
A Pine 30" dia., bears S.32°W., 43 lks. dist. mkd. 1/4 S12 BT.

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8872)

-----  
Intersect the old 1/4 sec. cor., which is a basalt stone, 15x10x8 ins., loosely set, marked and witnessed as described by the surveyor general. I change this cor. to refer to sec. 12 only and perpetuate it as follows: alongside the old cor. Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 cor. of sec. 12, T32S R10 only, with brass cap mkd.  
1/4  
S12  
1917  
from which  
A Sugar Pine 40" dia., bears S.42°W., 43 lks. dist. mkd. 1/4 S12 BT. (Old BT)  
A Laurel 5" dia., bears N.7°W., 46 lks. dist. mkd. 1/4 S12 BT. (New BT)