

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only, T32-10

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8862-63)

Set a stone 14x10x5 ins., 10" in the ground for the cor. to secs. 1, 6, 7 and 12, marked with 5 notches on the S. and 1 notch on the N. edges of same and from which

- A Laurel 8" dia., bears N.40°E., 47 lks. dist. mkd. T32S R9W S6 BT.
- A Fir 60" dia., bears S.80°E., 26 lks. dist. mkd. T32S R9W S7 BT.
- A Chinquapin 10" dia., bears S.60°W., 17 lks. dist. mkd. T32S R10W S12 BT.
- A Chinquapin 12" dia., bears N.70°W., 26 lks. dist. mkd. T32S R10W S1 BT.

GLO Survey by George S. Pershin, under Contract #728, Dated, Dec. 20, 1900 - (DCSO records Vol. 21 Page(s) 8866-67)

To a point 1.50 chs. N. and 2.30 chs. E. of old cor. which I totally obliterate.

Set a stone 15x12x5 ins., 10" in the ground for cor. of secs. 1, 12, 6 and 7 marked with 5 notches on S. and 1 notch on N. faces, from which

- A Fir 22" dia., bears N.14°E., 110 lks. dist. mkd. T32S R9W S6 BT.
- A Fir 34" dia., bears S.81°E., 62 lks. dist. mkd. T32S R9W S7 BT.
- A Fir 32" dia., bears S.13°W., 56 lks. dist. mkd. T32S R10W S12 BT.
- A Fir 44" dia., bears N.44°W., 76 lks. dist. mkd. T32S R10W S1 BT.

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8873)

Intersect the old cor. of secs. 1, 6, 7 and 12, which is a basalt stone 15x12x5 ins., loosely set, marked and witnessed as described by the surveyor general. I change this cor. to refer to secs. 1 and 12 only and perpetuate it as follows: alongside the old cor.

Set an iron post 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 1 and 12, T32S R10W only, with brass cap mkd.

T32S
 S1
 S12
 R10W 1917

(Cont. Next Page)

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 100572

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12 only, T32-10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which
A Fir 30" dia., bears S.11°W., 85 lks. dist. mkd. T32S
R10W S12 BT. (Old BT)
A Fir 40" dia., bears N.34°W., 19 lks. dist. mkd. T32S
R10W S1 BT. (Old BT)