

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 6 & 7 only (West)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8873)

-----  
Set an iron post 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 6 and 7, with brass cap mkd.

T32S  
S6  
S7  
R9W

1917

from which

A Fir 30" dia., bears N.84°E., 34 lks. dist. mkd. T32S R9W S6 BT.

A Fir 48" dia., bears S.14°E., 59 lks. dist. mkd. T32S R9W S7 BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - June 1967 - C.S. File 54/44-1

-----  
Found - 1917 GLO brass cap, properly mkd.  
30" now 40" D.Fir N.84°E., 22.4 ft., shows good scar.

48" now 60" D.Fir S.14°E., 38.9 ft., opened and found scribing.

New BT - 48" D.Fir S.76°E., 59.6 ft. mkd. T32S R9W S7 CS BT. (SE. tree is rotting.)

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 5/28/25 - C.S. File 67/60-39

-----  
Found - 2½" GLO Brass cap proj 12"  
32" D.Fir snag N.84°E. 21.0 ft (Rec 22.4 ft) fully healed single blaze Add 3½" mag nail left side center  
54" D.Fir snag S.14°E. 40.2 ft (Rec 38.9 ft) fd spike nail left side center. Illegible scribes visible on previously opened face.

38" D.Fir S.67°E. 58.7 ft (Rec S76°E. 59.6 ft) fd spike left side center fully healed double blaze.

New - ⅝"x30" Iron rod with D.C.S.O. yellow plastic cap, proj 3". Bears N.59°W. 12.5 ft.

Notes - Mon is approx 150 ft west of gravel rd.  
Mon is on steep SSW slope in old growth fir forest.

Compass decl. 14½°E.

OCRS COORDINATE SYSTEM

COTTAGE GROVE-CANYONVILLE ZONE

N. -7422.773 E. 35794.319