

| Alias | Description |
|-------|-------------|
| Alias | Description |
| Alias | Description |
| Alias | Description |

GLO survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 10, 1883 - (DCSO records Vol. 21 Page(s) 8863)

A Fir 36" dia., which I marked $\frac{1}{4}$ on W. side, for the $\frac{1}{4}$ sec. cor., from which

- A Fir 16" dia., bears N.70°E., 70 lks. dist. mkd. $\frac{1}{4}$ S BT
- A Fir 30" dia., bears S.50°W., 51 lks. dist. mkd. $\frac{1}{4}$ S BT

GLO Survey by George S. Pershin, under Contract #728, Dated, Dec. 20, 1900 - (DCSO records Vol. 21 Page(s) 8867)

Set a stone 18x10x7 ins., 12" in the ground for $\frac{1}{4}$ sec. cor. mkd. $\frac{1}{4}$ on W. face, from which

- A Fir 14" dia., bears S.85°E., 32 lks. dist. mkd. $\frac{1}{4}$ S6 BT
 - A Pine 10" dia., bears S.72°W., 48 lks. dist. mkd. $\frac{1}{4}$ S1 BT
- Obliterate old $\frac{1}{4}$ sec. cor.

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8874)

Intersect the old $\frac{1}{4}$ sec. cor., which is a basalt stone, 18x10x7 ins.; loosely set, marked and witnessed as described by the surveyor general. I change this cor. to refer to sec. 1 only and perpetuate it as follows: alongside the old cor. Set an iron post 3 ft. long, 1" dia., 26" in the ground, for $\frac{1}{4}$ cor. of sec. 1, T32S R10W only, with brass cap mkd.

$\frac{1}{4}$
S1
1917

from which

- A Sugar Pine 12" dia., bears S.71°W., 41 lks. dist. mkd. $\frac{1}{4}$ S1 BT. (New BT)
- A Hemlock 5" dia., bears N.62°W., 16 lks. dist. mkd. $\frac{1}{4}$ S1 BT. (New BT)