

PRIMARY CORNER DESCRIPTION NW Cor. Sec. 6, T32-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 1, 1883 - (DCSO records Vol. 21 Page(s) 8863)

Set a stone 14x12x8 ins., 10" in the ground for the cor. to Tps. 31 and 32 S., Rs. 9 and 10 W., marked with 6 notches on each edge, and from which
A Pine 36" dia., bears N.36°E., 78 lks. dist. mkd. T31S R9W S31 BT.
A Pine 18" dia., bears S.40°E., 59 lks. dist. mkd. T32S R9W S6 BT.
A Pine 36" dia., bears S.9°W., 154 lks. dist. mkd. T32S R10W S1 BT.
A Pine 30" dia., bears N.27°W., 88 lks. dist. mkd. T31S R10W S36 BT.

GLO survey by George S. Pershin, Deputy Surveyor, under Contract #728, dated Dec. 20, 1900 - (DCSO records Vol. 21 Page(s) 8867-68)

The old Tp. cor., which I obliterate, and Set a stone 18x16x7 ins., 12" in the ground for cor. of Tps. 32 S. Rs. 9 and 10 W. marked 6 notches on SE. and W. edges, also C.C., from which
A Fir 14" dia., bears S.24°E., 60 lks. dist., mkd. T32S R9W S6 CC BT.
A Fir 14" dia., bears S.23°W., 22 lks. dist. mkd. T32S R10W S1 CC BT.
This cor. is 35.10 chs. East of cor. of Tp. 31 S R.9 and 10 W.

GLO survey by Wm. H. Byars, Deputy Surveyor, under Contract #727, dated Dec. 20, 1900 - (DCSO records Vol. 19 Page(s) 8173)

Old Township corner - it and witness trees are still standing and agree with the field notes of the same furnished by the surveyor general. Destroy all marks referring to T31S Rs. 9 and 10 on post and witness trees along this line.

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 29 Page(s) 12196)

Intersect at the closing cor. of Tps. 32 S., Rs. 9 and 10 W., which is a basalt stone, 18x16x7 ins., loosely set, mkd. and witnessed as described by the surveyor general.
(Cont. Next Page)

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION NW Cor. Sec. 6, T32-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

I perpetuate this cor., as follows: alongside the old cor.
Set an iron post 3 ft. long, 3" dia., 24" in the ground, for
closing cor. of Tps. 32 S., Rs. 9 and 10., with brass cap
mkd.

T31S R9W

S 31

S 1 | S 6

R10W | R9W

C C

T 32 S

1917

from which

A Fir 16" dia., bears S.24°E., 60 lks. dist., mkd. T32S
R9W S6 CC BT. (Old BT)

A Fir 16" dia, bears S.23°W., 22 lks. dist. mkd. T32S R10W
S1 CC BT. (Old BT)

Douglas Co. Surveyors Office - John M. Powell, and crew -
June 6, 1967 - C.S. File 54/44-2

Found - 1917 GLO brass cap, properly marked.
16" now 20" Fir S.23°W., 15.7 ft., shows good scar.
16" Fir, found to be Pine snag, S.24°E., 39.6 ft.,
opened for scribing "R9"

New BT - 23" Fir S.43°E., 37.8 ft. mkd. T32S R9W S6 CS BT.