

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 109700

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 31 only, T31-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. H. Byars, Deputy Surveyor, under Contract #727, dated Dec. 20, 1900 - (DCSO records Vol. 19 Page(s) 8172-73)

Set a stone 18x12x6 ins., 12" in the ground, mkd. $\frac{1}{4}$ on N. face for the $\frac{1}{4}$ sec. cor. of sec. 31, from which

A Fir 18" dia., bears N.63°E., 50 lks. dist. mkd. S31 $\frac{1}{4}$ S BT.

A Fir 18" dia., bears S.35°E., 20 lks. dist. mkd. S31 $\frac{1}{4}$ S BT.

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 29 Page(s) 12195-96)

Intersect at the $\frac{1}{4}$ cor. of sec. 31, which is a basalt stone 18x12x6 ins., loosely set, mkd. and witnessed as described by the surveyor general, both BTs now being dead. I perpetuate this cor., as follows: alongside the old cor.

Set an iron post 3 ft. long, 1" dia., 26" in the ground for $\frac{1}{4}$ cor. of sec. 31, with brass cap mkd: $\frac{1}{4}$ S 31
1917

from which

A Fir 24" dia., bears N.78°30'E., 57 lks. dist., mkd. $\frac{1}{4}$ S31 BT. (New BT)

A Pinon 10" dia., bears N.7°W., 207 lks. dist. mkd. $\frac{1}{4}$ S31 BT. (New BT)