

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8919)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S\ 6}{S\ 7}$
1917

from which

A yew, 16" dia., bears S.61°W., 23 lks., mkd: 1/4 S7 BT.

A chinquapin, 5" dia. bears N.20°W., 52 lks. mkd: 1/4 S6 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J Brady - May 1967 - C.S. File 54/44-12

Found - GLO Brass Cap at 1/4 cor., properly mkd. in 1917.
5" chinquapin, now 7", N.20°W. 34.3 ft., rotted.
16" Yew, now 16", down & face rotted, S.61°W. 15.2 ft. scribe visible.

New BTs- 9" Chinquapin S.75°W. 31.7 ft. mkd. 1/4 S7 CS BT.

12" Pine N.13°E., 40.1 ft. mkd. 1/4 S6 CS BT.

Note - This cor. lies on top of small spur, approx. 275.0' W. & 125.0' North of creek.