

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 159700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32 only, T31-9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. H. Byars, Deputy Surveyor, under Contract #727, dated Dec. 20, 1900 - (DCSO records Vol. 19 Page(s) 8172)

-----  
Set a stone 16x10x5 ins., 12" in the ground for cor. to secs. 31 and 32, mkd. with 5 notches on the E. and 1 notch of the W. angles, from which  
A Yew 6" dia., bears N.15°E., 42 lks. dist. mkd. T31S R9W S32 BT.  
A Yew 6" dia., bears N.32°W., 49 lks. dist. mkd. T31S R9W S31 BT.

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 29 Page(s) 12195)

-----  
Intersect at the cor. of secs. 31 and 32, which is a basalt stone, 16x10x5 ins., loosely set, mkd. and witnessed as described by the surveyor general. I perpetuate this cor., as follows: alongside the old cor.  
Set an iron post 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 31 and 32, with brass cap mkd. 

T31S	R9W
S 31	S 32
1917	

  
from which  
A Yew 8" dia., bears N.16°E., 38 lks. dist. mkd. T31S R9W S32 BT. (Old BT)  
A Yew 8" dia., bears N.31°W., 47 lks. dist. mkd. T31S R9W S31 BT. (Old BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - May 1967 - C.S. File 54/32-84

-----  
Found - 1917 GLO brass cap, at sec. cor., properly mkd.  
8" now 9" Yew N.31°W., 32.6 ft. (Rec. 31 ft.) faint scribe visible "TS"  
8" now 8" Yew N.16°E., 36.5 ft. (Rec. 25.1 ft.) all scribing rotted off.  
New BTs- 21" D.Fir N.83°W., 42.5 ft. mkd. T31S R9W S31 CSBT  
38" D.Fir N.80°E., 42.0 ft. mkd. T31S R9W S32 CSBT  
This cor. lies on steep, N. slope, approx. 80 ft. S. of small creek and 660.0 ft. W. of Slide Creek.