

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8914)

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 7, 8, 17, & 18, with brass cap mkd

T32S R9W
S 7 | S 8
S 18 | S 17
1917

from which

- A sugar pine, 40" dia., bears N.46°E., 39 lks., mkd: T32S R9W S8 BT.
- A fir, 40" dia., bears S.22°E., 74 lks., mkd: T32S R9W S17 BT.
- A chinquapin, 18" dia., bears S.87°W., 39 lks., mkd: T32S R9W S18 BT.
- A chinquapin, 18" dia., bears N.57°W., 71 lks., mkd: T32S R9W S7 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J Brady - June 1967 - C.S. File 54/44-20

-
- Found - GLO Brass Cap, 1917, properly marked at Corner.
- 18" Chinquapin, now 18" Snag, N.57°W. 46.9 ft., shows scribing.
 - 40" Pine, now 42" Snag, N.46°E. 25.7 ft., shows scribing.
 - 40" Fir, now 42", S.22°E. 48.8 ft., shows good face.
 - 18" Chinquapin, now down, S.87°W. 25.7 ft shows face
- New BTs-
- 14" D.Fir N.80½°W. 67.7 ft. mkd. T32S R9W S7 CS BT.
 - 6" D.Fir N.34°E. 28.0 ft. mkd. T32S R9W S8 CS BT.
 - 14" Chinquapin S.74°W. 43.3 ft mkd T32S R9W S18 CSBT