

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5, 6, & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8917)

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 5, 6, 7, & 8, with brass cap mkd

T32S R9W
S 6 | S 5
S 7 | S 8
1917

from which

A chinquapin, 8" dia., bears N.67°E., 30 lks., mkd: T32S R9W S5 BT.

A chinquapin, 7" dia., bears S.31°E., 24 lks., mkd: T32S R9W S8 BT.

A pinon, 9" dia. bears S.39°W., 28 lks mkd: T32S R9W S7 BT

A fir, 6" dia., bears N.7°W., 11 lks., mkd: T32S R9W S6 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J Brady - June 1967 - C.S. File 54/44-21

Found - GLO Brass Cap, 1917, properly marked at corner.
9" now 10" Pine, S.39°W. 18.5 ft., burnt face, scribe visible, "T32S" "W" other marks not legible.

No other PT's. found.

New BTs- 8" D.Fir S.63°W. 15.2 ft. mkd. T32S R9W S7 CS BT.

15" Pine N.70°W. 20.3 ft. mkd. T32S R9W S6 CS BT.

15 D.Fir S.70°E. 14.0 ft. mkd. T32S R9W S8 CS BT.

5" Chinquapin N.69½°E. 19.5 ft. mkd. S5 CS BT.

Note - This corner lies 20.0 ft. south of small ravine.