

PRIMARY CORNER DESCRIPTION A P on N. bdy. Sec. 5

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Richmond S. Dickerson, Deputy Surveyor, under Contract #474, dated May 10, 1883 - (DCSO records C.S. File 64/76-2)

Set a stone 15x10x8 ins., 10" in the ground for the cor. to secs. 5, 6, 31 and 32 mkd. with 5 notches on the E. and 1 notch on the W. edge, and from which
A Laurel 5" dia., bears N.65°E., 22 lks. dist. mkd. T31S R9W S32 BT.
A Fir 18" dia., bears S.25°E., 47 lks. dist. mkd. T32S R9W S5 BT.
A Fir 55" dia., bears S.45°W., 17 lks. dist. mkd. T32S R9W S6 BT.
A Laurel 8" dia., bears N.63°W., 25 lks. dist. mkd. T31S R9W S31 BT.

GLO survey by Wm. H. Byars, Deputy Surveyor, under Contract #727, dated Dec. 20, 1900 - (DCSO records Vol. 19 Page(s) 8172)

Cor. of secs. 5 and 6. Corner and witness trees standing.

GLO Resurvey by Fred Mensch and Gerald A. Sorrels, Surveyors under Special Instructions, Group #35, dated Dec. 22, 1916 - (DCSO records Vol. 29 Page(s) 12194)

Intersect at point for old cor. of secs. 5 and 6, located by reference to the BTs as described by the surveyor general. The NE. BT is defaced by fire, the SE. tree is dead and the NW. tree is dead and fallen. I change this cor. to an angle point and perpetuate it as follows: at the exact cor. point
Set an iron post 3 ft. long, 1" dia., 26" in the ground, for angle point, with brass cap mkd. AP
1917
from which
A Fir 36" dia., bears S.45°W., 17 lks. dist. mkd. AP BT. (Old BT)
A Fir 36" dia., bears N.11°W., 25 lks. dist. mkd. AP BT. (New BT)

Douglas Co. Surveyors Office - John M. Powell, and crew - May 1967 - C.S. File 54/32-88

Found - 36" now 38" D.Fir N.11°W., 16.5 ft., shows good scar.
(Cont. Next Page)

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 206700

PRIMARY CORNER DESCRIPTION A P on N. Bdy. Sec. 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

36" now 38" D.Fir S.45°W., 11.2 ft., bark scribe visible, "T32 R W", broken in half.
1917 GLO brass cap, properly marked.
New BT - 18" D.Fir S.26W., 24.0 ft. mkd. AP CS BT.
A.P. cor. lies 349.8 ft. East of sec. cor. to secs. 5 & 6 only, T32-9