

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8918)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor., with brass cap marked

$\frac{1}{4} \frac{S \ 5}{S \ 8}$
1917

from which

- A fir, 18" dia., bears S.23°E., 24 lks., mkd: 1/4 S8 BT.
- A fir, 24" dia., bears N.14°W., 7 lks., mkd: 1/4 S5 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J Brady - June 1967 - C.S. File 54/44-43

Found - GL0 Brass Cap at 1/4 Corner mkd: In 1917.
18", now 35" D.Fir, S.23°E. 15.8 ft. , shows scar.
24", D.Fir, now 24" Snag, N.14°W. 4.7 ft., scribing visible.

New BT - 6" D.Fir N.80°E. 56.5 ft. mkd: 1/4 S5 CS BT.

Note - This corner lies 20.0 ft. south of old road in cut unit.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 5/13/2025 - C.S. File 67/60-31

Found - 2 1/2" GL0 brass cap proj. 1"
Badly rotted 30"x2 1/2' D.Fir stump S.23°E. 15.8 ft
(slope dist) 14° horiz.
17" D.Fir N.80°E. 56.5 ft fully healed single blaze
Tree on top of high cut bank.

New - 48" D.Fir S.43°E. 14.3 ft not scribed. 3 1/2" mag nail,
right side center.

Note - Corner 20 ft south of old road.
Compass decl. 14 1/2°E.
GIS MAP LOCATION
42.81180 N.
123.78526 W.