

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8907-8)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor., with brass cap marked

1/4
S 8 | S 9
1917

from which

- A fir, 18" dia., bears N.68°E., 31 lks., mkd: 1/4 S9 BT.
- A fir, 30" dia., bears N.70°W., 40 lks., mkd: 1/4 S8 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J Brady - May 1967 - C.S. File 54/44-9

Found - GLO Brass Cap at Cor., properly mkd. in 1917.
18" D.Fir, now 20" Snag, N.68°E. 20.5 ft., shows good scar.

30" D.Fir, now stump, N.70°W. 26.4 ft.
New BTs- 5" Chinq. S.72°E. 15.4 ft. mkd. 1/4 S9 CS BT.
19" D.Fir N.61°W. 102.7 ft. mkd. 1/4 S8 CS BT.

Note - This cor. lies 250.0 ft. W. of logging road & about 85.0 ft. N. of small ravine in heavily logged area.