

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8908)

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 4, 5, 8, & 9, with brass cap mkd

T32S R9W
S 5 | S 4
S 8 | S 9
1917

from which

- A fir, 16" dia. bears N.47°E., 16 lks. mkd: T32S R9W S4 BT
- A chinquapin, 14" dia., bears S.31°E., 12 lks., mkd: T32S R9W S9 BT.
- A fir, 40" dia. bears S.10°W., 41 lks. mkd: T32S R9W S8 BT
- A fir, 20" dia. bears N.74°W., 41 lks. mkd: T32S R9W S5 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J Brady - May 1967 - C.S. File 54/44-8

Found - GLO Brass Cap at Cor., properly mkd. in 1917.
16", now 18" D.Fir, N.47°E. 10.6 ft., opened for scribe "W".
20", now 23" D.Fir, N.74°W. 27.1 ft. shows good scar
40", now 41" D.Fir S.10°W. 27.1 ft., shows good scar
SE Chinquapin down & rotten.

New BT - 21" D.Fir S.40°E. 26.6 ft. mkd. T32S R9W S9 CS BT.