

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 5

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8910)

-----  
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor., with brass cap marked

1/4  
S 5 | S 4  
1917

from which

- A fir, 36" dia., bears S.62°E., 41 lks., mkd: 1/4 S4 BT.
- A fir, 36" dia., bears N.24°W., 32 lks., mkd: 1/4 S5 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J Brady - May 1967 - C.S. File 54/44-11

-----  
Found - GLO Brass Cap at 1/4 Cor., 1917 properly marked.  
36" D.Fir, now 40" Snag, S.62°E. 27.1 ft., badly burnt face.

36" D.Fir, now 40" Snag, N.24°W. 21.1 ft., opened for scribing "1/4".

New BTs- 5" Laurel N.38 1/2°W. 20.7 ft. mkd. 1/4 CS BT.  
5" Chinquapin S.89°E. 11.6 ft. mkd. CS BT.

Note - No other larger trees available.  
Corner lies on E edge of N-S ridge in burnt & very brushy area. All Trees Tagged.