

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8909)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S\ 4}{S\ 9}$
1917

from which

A fir, 30" dia., bears S.77°W., 87 lks., mkd: 1/4 S9 BT.

A fir, 36" dia., bears N.40°W., 102 lks., mkd: 1/4 S4 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J Brady - May 1967 - C.S. File 54/44-6

Found - GLO Brass Cap at Cor., properly mkd. in 1917.
30", now 39" D.Fir, S.74°W. (Record S.77°W.) 57.4 ft., shows good scar.

36" D.Fir, now 47" Stump, N.40°W. 67.3 ft., shows good scar.

New BT - 14" D.Fir N.4°E. 8.2 ft. mkd. 1/4 S4 CS BT.