

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Cor. SEcs 15, 16, 21, & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8897-8)

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 15, 16, 21, & 22, with brass cap mkd

	T32S	R9W
	S 16	S 15
	S 21	S 22
	1917	

from which

- A chinquapin, 14" dia., bears N.48°E., 16 lks., mkd: T32S R9W S15 BT.
- A chinquapin, *5 14" dia., bears S.72°E., *2 12 lks., mkd: T32S R9W S22 BT. (*14" not 5" and 12 lks not 2 lks per research 6/10/2025 JC DCSO)
- A fir, 36" dia. bears S.60°W. 30 lks. mkd: T32S R9W S21 BT
- A fir, 30" dia. bears N.62°W. 32 lks. mkd: T32S R9W S16 BT

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 6/11/2025 - C.S. File 67/60-42

Found - 2½" Brass cap on Iron pipe partially buried. Tipped straight down hill. BT measured to base of pipe.
15" Chinquapin S.72°E. 7.9 ft (Rec 12 lks) partly healed, face rotted. Add 3½" mag nail right side center.
42"x2 ft sawn D.Fir stump. S.60°W. 19.8 ft (Rec 19 lks) fully healed single blaze. Add 6" spike top center.
37" D.Fir N.62°W. 21.1 ft (Rec 32 lks) fully healed single blaze. Add 3½" mag nail, right side center.

Reset - Reference mon base reset mon with cap at reference position. Proj. 10" rough stone mound constructed around base of mon.

New - 5" chinquapin south 10.9 ft Scribed "X" BT on double blaze. 3½ mag nail, right side center.

Notes - Mon approx 150 ft west of gravel road.
Mon on steep W.S.W. slope in very old thinned fir and chinquapin.

Compass decl. 14½°E.
Trimble Geo XT Position
42°46'58.494"N.
123°45'20.730"W.