TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8899)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for ¼ sec. cor., with brass cap marked

¼
S 16|S 15
1917

from which
A fir, 30" dia., bears S.88°E., 49 lks., mkd: ¼ S15 BT.
A fir, 16" dia., bears N.34°W., 27 lks., mkd: ¼ S16 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Joe Brady - July 1967 - C.S. File 54/44-70

Found - Rod of GLO Brass Cap. Corner is close to campground.
30", now 35" D.Fir S.88°E. 32.3 ft. shows good scar.
16", now 24" D.Fir, N.34°W. 17.8 ft. shows good scar
Set Brass Cap at ¼ Corner mkd: County Surveyors T32S R9W
Office, 1967 ¼ S 16|S 15
Bearing Trees are tagged and in good condition.
Note - This corner lies 70.0 ft. N. of high ridge running E. & W. & approx. 300' N. of Cold Spring Campground Road. Location Tag on S. side of Road.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 6/2/2025 - C.S. File 67/60-40

Found - 2½" D.C.S.O. Brass cap proj 15" in rough stone mound around base.
41" D.Fir S.85°E. (Rec S.88°E.) 32.3 ft fully healed single blaze.
35" D.Fir N.31°W. (Rec N.34°W.) 17.8 ft fully healed single blaze.
New - 5" D.Fir N.67°E. 8.0 ft scribed "X' BT on double blaze
7" D.Fir S.22°W. 10.3 ft scribed "X" BT on double blaze.
Notes - Mon is 100ft± N. Of dirt road on the high ridge running E.E.W.
Compass decl. 14½°E.
OCRS COORDINATE SYSTEM
COTTAGE GROVE-CANYONVILLE ZONE
N. -15484.453 E. 50664.627