TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8901)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for ¼ sec. cor., with brass cap marked

¼
S 9 | S 10
1917

from which
A yew, 7" dia., bears N.30°E., 20 lks., mkd: ¼ S10 BT.
A chinquapin, 12" dia. bears N.87°W., 27 lks. mkd: ¼ S9 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J. Brady - May 1967 - C.S. File 54/44-7

Found - GLO Brass Cap at corner, properly marked in 1917.
7", now 8" Yew, N.30°E., 13.2 ft., tree rotted, scribe marks not legible.
12", now 15" Chinquapin, N.87°W. 17.8 ft., rotten face, "4 39" visible.
New BTs- 9" Chinquapin N.62°E., 3.8 ft. mkd. ¼ S10 CS BT
14" Chinquapin S.31°W., 24.4 ft. mkd. ¼ S9 CS BT.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 5-18-2025 - C.S. File 67/60-30

Found - 2½" GLO brass cap up 6".
28" chinquapin N.87°W. 17.8 ft fully healed single blaze. Add 3½" mag nail, right side center.
29" chinquapin S.31°W. 24.4 ft. Scribes "S 9 CS BT" visible on portion of blaze exposed by lightning scar. Add 3½" mag nail right side center.
New - 10" D.fir N.41°E. 18.2 ft scribed "¼ S10 BT" on double blaze. 3½" mag nail right side center.
4" D.fir S.38°E. 2.2 ft scribed "X" BT on double blaze. 3½" mag nail right side center.
Notes - Mon. is approx. 150'± east of stockpile pad which is north of gravel road.
Mon. on moderate east slope in old regrowth forest.
Compass decl. 14½°E.
OCRS COORDINATE SYSTEM
COTTAGE GROVE-CANYONVILLE ZONE
N. 42°48'16.60636" W. 123°45'20.66944"