

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8901-2)

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 3, 4, 9, & 10, with brass cap mkd

T32S R9W
S 4 | S 3
S 9 | S 10
1917

from which

- A fir, 20" dia. bears N.61°E., 35 lks. mkd: T32S R9W S3 BT
- A yew, 14" dia. bears S.68°E. 58 lks. mkd: T32S R9W S10 BT
- A fir, 20" dia. bears S.72°W., 55 lks. mkd: T32S R9W S9 BT
- A fir, 18" dia. bears N.26°W., 37 lks. mkd: T32S R9W S4 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J. Brady - May 1967 - C.S. File 54/44-5

Found - GLO Brass Cap at corner, properly marked in 1917.
20", now 23" D.Fir, N.61°E. 23.1 ft. shows good scar
20", now 26" D.Fir, S.72°W. 36.3 ft. shows good scar
18", now 22" D.Fir, N.26°W. 24.4 ft. shows good scar
14", now 20" Yew, S.66°W. 39.3 ft. (Record S.68°W. 38.3') (faint scribe visible "3 S" face badly rotted)

Reblazed. & Rescribed -

20" Yew S.66°W. 39.3 ft. mkd. T32S R9W S10 CS BT.

Note - This corner lies approx. 200.0 ft E of logging road.
Brass Cap is flush with ground.
All trees tagged & location tag on road.