

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8903)

-----  
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor., with brass cap marked

1/4  
S 4 | S 3  
1917

from which

- A fir, 18" dia., bears S.46°E., 41 lks., mkd: 1/4 S3 BT.
- A fir, 20" dia., bears S.68°W., 46 lks., mkd: 1/4 S4 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J Brady - May 1967 - C.S. File 54/44-4

-----  
Found - GLO Brass Cap at 1/4 Corner properly mkd in 1917.  
18", now 19" D.Fir S.46°E. 26.4 ft. shows good scar.  
20" D.Fir S.68°W. 30.4 ft falls in skid road, No trace.

New BT - 46" D.Fir N.4 1/2°W. 31.0 ft. mkd. 1/4 S4 CS BT.