

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8898)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S\ 15}{S\ 22}$
1917

from which

A fir, 16" dia., bears N.39°E., 89 lks., mkd: 1/4 S15 BT.
A fir, 40" dia., bears S.57°E., 70 lks., mkd: 1/4 S22 BT.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 6/9/2025 - C.S. File 67/60-43

Found - 2 1/2" GL0 brass cap broken off Iron pipe. 1" O.D. pipe near plum in ground.

35" D.Fir N.46°E. 58.5 ft (Rec N.39°E. 89 lks) fully healed single blaze. Add 3 1/2" mag nail right side center.
50" D.Fir S.50°E. 47.0 ft (Rec S.57°E. 70 lks) fully healed single blaze. Add 3 1/2" mag nail right side center.

Set - 2 1/2" alum cap on 5/8"x30" iron rod, proj 4" on west edge of fd pipe plum position.

DOUGLAS COUNTY

T32S R9R

1/4 S15

S22

2025

SURVEYORS OFFICE

New - 1917 brass cap and broke iron pipe set on north edge of new monument.

13" D.Fir N.16°E. 25.0 ft scribed 1/4 S15 BT on double blaze. 3 1/2" mag nail right side center.

18" D.Fir S.34°W. 8.5 ft scribed 1/4 S22 BT on double blaze. 3 1/2" mag nail right side center.

Notes - Mon is 250± ft east of gravel road.

Mon on moderate east slope in older reprod.

Compass decl. 14 1/2°E.

Trimble Geo XT Position

42°46'58.483"N.

123°44'45.480"W.