

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8900)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S\ 10}{S\ 15}$
1917

from which

A fir, 8" dia., bears N.65°E., 51 lks., mkd: 1/4 S10 BT.

A sugar pine, 8" dia. bears S.81°W., 56 lks. mkd: 1/4 S15 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J. Brady - June 1967 - C.S. File 54/44-24

Found - GLO Brass Cap, 1917, properly marked for 1/4 corner. 8", now 28" D.Fir, N.64°E. 33.7 ft., shows a face.

8" S.Pine, now down, S.81°W. 37.0 ft., down & rotted

Rescribed: 28" D.Fir N.65°W. 33.7 ft. Mkd. 1/4 S10 CS BT.

New BT - 12" D.Fir S.16°W. 10.7 ft. mkd. 1/4 S15 CS BT.