

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION WC 1/4 Cor. Secs. 3 & 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8902)

Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor., with brass cap marked

1/4 $\frac{S \ 3}{S \ 10}$
1917

from which

A fir, 48" dia., bears N.25°E., 20 lks., mkd: 1/4 S3 BT.

A fir, 30" dia., bears S.16°W., 33 lks., mkd: 1/4 S10 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J. Brady - June 1967 - C.S. File 54/44-25

Found - Orig. 48", now 53" Fir, N.25°E. 13.2 ft., opened for scribing, scribe visible.

No trace of 30" Fir to SW in roadway.

Do not find U.S. GLO Brass Cap as corner lies along East edge of Jeep Road.

Set Brass Cap at Cor. Mkd: County Surveyors T32S R9W
Office WC 10 ft W to
1967 1/4 $\frac{S \ 3}{S \ 10}$

New BTs- Chinguapin S.75°E. 13.6 ft. Mkd. WC 1/4 S10 CS BT.

7" pine N.14°W. 24.2 ft. mkd. WC 1/4 S3 CS BT.