

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Cor. Secs. 14, 15, 22, & 23

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8891)

-----  
Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 14, 15, 22, & 23, with brass cap mkd

T32S R9W  
S 15 | S 14  
S 22 | S 23  
1917

from which

- A fir, 40" dia. bears N.51°E. 98 lks. mkd: T32S R9W S14 BT
- A fir, 36" dia. bears S.47°E. 49 lks. mkd: T32S R9W S23 BT
- A fir, 36" dia. bears S.53°W. 37 lks. mkd: T32S R9W S22 BT
- A fir, 24" dia. bears N.43°W. 37 lks. mkd: T32S R9W S15 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J. Brady - June 1967 - C.S. File 54/44-14

-----  
Found - 40" now 46" D.Fir, N.51°E. 64.7 ft., shows good scar  
36" now 41" D.Fir, S.53°W. 24.4 ft., shows good scar  
24" now 38" D.Fir, N.43°W. 24.4 ft., shows good scar  
36" D.Fir, now 40" Snag, S.47°E. 32.3 ft., shows good scar.

GLO Brass Cap, 1917, properly marked at corner.

New BT - 6" D.Fir S.26°E. 27.1 ft. mkd. T32S R9W S23 CS BT.  
Note - This corner lies approx. 180.0 ft. south of logging road.