

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8893)

Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 10, 11, 14, & 15, with brass cap mkd

T32S R9W
S 10|S 11
S 15|S 14
1917

from which

- A chinquapin, 7" dia., bears N.30°E., 26 lks., mkd: T32S R9W S11 BT.
- A sugar pine, 48" dia., bears S.5°E., 33 lks., mkd: T32S R9W S14 BT.
- A fir, 48" dia., bears S.52°W., 132 lks., mkd: T32S R9W S15 BT.
- A laurel, 5" dia., bears N.61°W., 53 lks., mkd: T32S R9W S10 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J. Brady - June 1967 - C.S. File 54/44-26

Found - GLO Brass Cap, 1917, properly marked for ¼ corner.
7" now 11" Chinquapin, N.30°E. 17.2 ft., shows scribing.
48" now 68" S.Pine Snag, S.5°E. 21.8 ft., shows scribing.
48" now 70 D.Fir, S.52°W., 87.1 ft. shows good face.
5" now 8" Laurel, N.61°W., 35.0 ft. shows good face.
New BT - 12" D.Fir S.67°E., 5.2 ft. mkd. T32S R9W S11 CS BT.