

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8895)

-----  
Set an iron post, 3 ft. long, 2" dia., 24" in the ground, for cor. of secs. 2, 3, 10, & 11, with brass cap mkd

T32S R9W  
S 3 | S 2  
S 10 | S 11  
1917

from which

- A fir, 48" dia. bears N.79°E., 78 lks. mkd: T32S R9W S2 BT
- A fir, 40" dia. bears S.65°E. 88 lks. mkd: T32S R9W S11 BT
- A fir, 30" dia. bears S.40°W. 88 lks. mkd: T32S R9W S10 BT
- A fir, 40" dia. bears N.72°W., 33 lks. mkd: T32S R9W S3 BT

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & Joe Brady - July 1967 - C.S. File 54/44-59

- 
- Found - GLO Brass Cap properly marked in 1917.  
48" now 52" D.Fir, N.79°E., 51.5 ft., shows good scribing.  
40" D.Fir, now 48" Snag, S.65°E., 58.1 ft., shows good scar.  
30" now 37" D.Fir, S.40°W. 58.1 ft., shows god scar.
- New BT - 6" Laurel S.45½°E. 18.7 ft. mkd. ¼ S11 CS BT.
- Note - This corner lies on steep south slope.