

TOWNSHIP 32 RANGE 09 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 3

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Dependent survey by Fred Mensch & Gerald A. Sorrels, Dep. Surveyors under special instructions dated Dec. 22, 1916 - (DCSO records Vol. 21 Page(s) 8897)

-----  
Set an iron post, 3 ft. long, 1" dia., 26" in the ground, for 1/4 sec. cor., with brass cap marked

1/4  
S 3 | S 2  
1917

from which

- A fir, 8" dia., bears N.81°E., 25 lks., mkd: 1/4 S2 BT.
- A fir, 10" dia., bears S.85°W., 21 lks., mkd: 1/4 S3 BT.

Douglas Co. Surveyors Office - John M. Powell - Frank Jones & J Brady - July 1967 - C.S. File 54/44-61

-----  
Found - GLO brass cap properly marked in 1917.  
8" now 10" D.Fir N.81°E., 16.5 ft. shows good scar.  
10" D.Fir, now 11" stob, S.85°W., 13.9 ft., shows scribing.

New BT - 16" D.Fir N.76°W., 17.8 ft., mkd: 1/4 S3 CS BT.